

ALIS

NATURAL OIL FOR EXTERIOR WOOD

Perfect for outdoor wood, roasted wood, garden furniture, and patios, this protective oil for outdoor wood offers great value.



Sesame



Light Teak



Elm Dark Brown



Black

A BEAUTIFUL, SIMPLE AND NATURAL SOLUTION!

Biodegradable, ecological, non-toxic and natural, our wood-impregnating oils are perfect for all your outdoor projects. Economical per square foot, ALIS Decking Oil saturates wood to repel water and resist weather, sun and mould. Livos wood oils are easy to apply and maintain for professional results, every time.

- Does not peel and requires no sanding for maintenance.
- Superior protection against UV rays. Important: the 002-Clear has no UV protection, and the 004-Natural has limited UV protection.
- Easy to apply with a roller, brush, or spray gun.
- Exceptional coverage of 50 to 100 square feet per liter for two coats.
- Excess layers require much less product for cost-effective application.
- A highly effective natural protective oil.
- Weather-resistant and recognized by professionals.



LEISURECRAFT.COM



COVERAGE CAPACITY

For reference only*

SIZE	SQ FT	1 COAT	2 COATS	TOTAL QTY
10 X 10	100 sq ft	0.80 liters	0.41 liters	1.21 liters
20 X 20	400 sq ft	3.20 liters	1.65 liters	4.85 liters
20 X 30	600 sq ft	4.70 liters	2.45 liters	7.15 liters

*Quantities may vary depending on the type of wood, as well as the age and preparation of the surface.

SUITABLE FOR ALL TYPES OF WOOD*

1 SURFACE PREPARATION

***IMPORTANT :** Let cedar and treated wood (green or brown) age for a minimum of 6 months before treatment.

The wood must be completely dry, free of dust, and absorbent. We recommend removing the mill glaze from the wood by sanding with 100-grit paper. Apply at temperatures above 10°C and ensure that the temperature remains above 10°C for at least 8 hours after application. The wood's moisture content should be between 12% and 18%.

2 OIL APPLICATION

FIRST COAT

Stir the product thoroughly with a stick to ensure the pigmentation is well mixed with the oil. **Test on a small area to confirm your color.** Apply with a brush, spray gun, or roller to ensure the wood is well saturated. Even out excess oil after 5 minutes, if necessary. Wait approximately 18 hours before applying the second coat.

2SECOND COAT

Apply more thinly and even out excess oil with a brush after about 5-10 minutes.

3 CLEANING AND MAINTENANCE

Clean with GLOUROS 1806 and reapply ALIS 579 oil as soon as the finish shows signs of wear or becomes extremely dull. Ideally, perform this maintenance once a year on terraces and every 3 to 5 years on cladding.

IMPORTANT

BEFORE STARTING THE OILING PROCESS

Our products are colored with natural pigments, so color variations between batches may occur. Therefore, it is recommended to perform a color test on a small section of your project before proceeding with the full application. Make sure the result meets your expectations before continuing.

Additionally, the type, preparation, and age of the wood can significantly affect the final shade. We are not responsible for the color achieved if no test is performed or if shades are mixed.

DO NOT APPLY IN DIRECT SUNLIGHT.

THE LIABILITY OF THE DISTRIBUTOR AND MANUFACTURER IS LIMITED TO THE VALUE OF THE PRODUCT.

USAGE PRECAUTIONS

To prevent spontaneous combustion, cloths, polishing pads, and applicators soaked in oil should be kept away from air by placing them in a tightly sealed metal container or immersed in water before disposal.



RECOMMENDATION - MAINTENANCE

Since our products are made from natural ingredients, only **GLOUROS 1806** cleaner is recommended for cleaning. Any other cleaning or surface preparation products may cause adhesion issues.